



NOTE: All relevant materials are complied with RoHS directive .

④	4	BLACK HEAT SHRINK TUBE ϕ 2.0*20mm	A4HA09-0959	2	M959
③	3	BLACK HEAT SHRINK TUBE ϕ 3.0*28mm	A4HA10-0959	1	M959
		UL1061 26AWG INSULATOR WIRE, JACKET WHITE(83mm*1PCS), RED(83mm*1PCS), OD 1.0mm DRAWING NO.EH002601C-013	H5SE06-0304	2	M304
	2	TERMINAL: CKM2542-T	A1RJ44-0031	2	M31
		HOUSING: CKM2542-2P, PITCH 2.54mm	A1RJ17-0031	1	M31
	1	SWITCH: RED PUSHBUTTON <PB-05-7R1-G>	A7KA22-1323	1	T1323
	No.	DESCRIPTION		Q'TY	Supplier

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm \pm 10mm 201~1000mm \pm 20mm 1001 ~1500mm \pm 25mm 1501~2100mm \pm 30mm 2100mm \uparrow \pm 40mm		
CHECKED	HU				
DESINGER	LPQ				
DRAWING	YNAG				
DATE	22/MAY/24	ITEM NO.	CAS-T001-HNS-0320	UNIT:mm	

④	REV.2	2024.05.22	TAKE OFF TRANSPARENT HEAT SHRINK TUBE & MODIFY BLACK HEAT SHRINK TUBE	CHECKED	
③	REV.1	2023.11.22	MODIFY CUTTING LENGTH		