



P1	P2	
1	1	RED
2	3	BLACK
3	2	GREEN
4	4	BLUE

NOTE: All relevant materials are complied with RoHS directive .

4	BLACK HEAT SHRINK TUBE ϕ 1.0*35mm	A4HA09-0959	4	M959
3	BLACK HEAT SHRINK TUBE ϕ 4.0*30mm	A4HA54-0959	1	M959
	UL1061 28AWG INSULATOR WIRE, JACKET BLACK(85mm*1PCS), GREEN(85mm*1PCS), RED(85mm*1PCS),BLUE(85mm*1PCS), OD 0.9mm DRAWING NO.EH002801C-024	H5SE07-0304	2	M304
2	TERMINAL: CKM2542-T	A1RJ44-0031	4	M31
	HOUSING: CKM2542-2*2P, PITCH 2.54mm	A1RJ20-0031	1	M31
1	LED(L-154A4SUREQBFZGEW)		1	M633
No.	DESCRIPTION		Q'TY	Supplier

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm \pm 10mm 201~1000mm \pm 20mm 1001 ~1500mm \pm 25mm 1501~2100mm \pm 30mm 2100mm \uparrow \pm 40mm
CHECKED	HU		
DESINGER	LPQ		
DRAWING	YANG		
DATE	29/AUG/24		
ITEM NO.	CAS-T001-HNS-0359-1	UNIT:mm	

CHECKED