




Technical Specification



EIA WR	WR28
Frequency Range(GHz)	26.5 – 40.0
Coupling(dB)	30
Coupling Accuracy(dB)	±1.0 Max.
Freq. Sensitivity(dB)	±0.9 Max.
Directivity(dB)	30 Min.
Insertion Loss(dB)	0.3 Max. (Not including the theoretical loss 8.69×10^{-3} dB)
Mainline VSWR	1.10:1 Max.
Secondline VSWR	1.15:1 Max.
Flange	FBP320(UBR320)
Material	Cu
Size(mm)	203.2 x 19.1 x 56.9
Net Weight(Kg)	0.45 Around

Outline Drawing (Size: mm)



AINFO Inc.


Page 1 of 6

China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA : Tel: (+1) 949-639-9688,

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)



FBP320

AINFO Inc.

Page 2 of 6


China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA : Tel: (+1) 949-639-9688,

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results


Coupling Port 1




Port 2




Directivity Port 1




Port 2



I.L. (Including the theoretical loss 8.69×10^{-3} dB)




Mainline VSWR



Secondline VSWR

Port 1



Port 2

