



1200V/30A Silicon Carbide Power Schottky Barrier Diode

Features

- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation


Key Characteristics		
VRRM	1200	V
IF, $T_c \leq 127^\circ\text{C}$	30	A
QC	125	nC

Benefits

- Unipolar rectifier
- Substantially reduced switching losses
- No thermal run-away with parallel devices
- Reduced heat sink requirements

Applications

- SMPS, e.g., CCM PFC;
- Motor drives, Solar application, UPS, Wind turbine, Rail traction, EV/HEV



Part No.	Package Type	Marking
G5S12030PMT	TO-247AC	G5S12030PMT

Maximum Ratings



Parameter	Symbol	Test Condition	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}		1200	V
Surge Peak Reverse Voltage	V_{RSM}		1200	
DC Blocking Voltage	V_{DC}		1200	
Continuous Forward Current	I_F	Tc=25℃ Tc=125℃ Tc=127℃	57 31 30	A
Repetitive Peak Forward Surge Current	I_{FRM}	Tc=25℃, tp=10ms, Half Sine Wave, D=0.3	150	A
Non-repetitive Peak Forward Surge Current	I_{FSM}	Tc=25℃, tp=10ms, Half Sine Wave	200	A
Power Dissipation	P_{TOT}	Tc=25℃	224	W
		Tc=110℃	97	W
Operating Junction	T_j		-55℃ to 175℃	℃
Storage Temperature	T_{stg}		-55℃ to 175℃	℃
Mounting Torque		M3 Screw 6-32 Screw	1 8.8	Nm lbf-in

Thermal Characteristics


Parameter	Symbol	Test Condition	Value	Unit
			Typ.	
Thermal resistance from junction to case	$R_{th JC}$		0.67	℃/W

Electrical Characteristics(Per leg)


Parameter	Symbol	Test Conditions	Numerical		Unit
			Typ.	Max.	
Forward Voltage	V_F	$I_F=30A, T_J=25^{\circ}C$	1.53	1.7	V
		$I_F=30A, T_J=175^{\circ}C$	2.37	2.5	
Reverse Current	I_R	$V_R=1200V, T_J=25^{\circ}C$	4.31	50	μA
		$V_R=1200V, T_J=175^{\circ}C$	2.26	100	
Total Capacitive Charge	Q_C	$V_R=800V, T_J=150^{\circ}C$ $Q_C = \int_0^{V_R} C(V)dV$	125	-	nC
Total Capacitance	C	$V_R=0V, T_J=25^{\circ}C, f=1MHz$	1828	-	pF
		$V_R=400V, T_J=25^{\circ}C, f=1MHz$	112	-	
		$V_R=800V, T_J=25^{\circ}C, f=1MHz$	92	-	

Performance Graphs(Per leg)1) Forward IV characteristics as a function of T_J :2) Reverse IV characteristics as a function of T_J :


3) Current Derating:



4) Capacitance vs. reverse voltage:



Package TO-247AC



Note:

1. Package Reference: JEDEC TO247, Variation AD.
2. All Dimensions Are In mm.
3. Slot Required, Notch May Be Rounded
4. Dimension D & E Do Not Include Mold Flash. Mold Flash Shall Not Exceed 0.127mm Pre Side. These Dimensions Are Measured At The Outermost Extreme Of The Plastic Body.
5. Thermal Pad Contour Optional Within Dimension D1 & E1.
6. Lead Finish Uncontrolled In L1.
7. ØP To Have A Maximum Draft Angle Of 1.5° To The Top Of The Part With A Maximum Hole Diameter Of 3.91mm.
8. Dimension "b2" And "b4" Does Not Include Dambar Protrusion. Allowable Dambar Protrusion Shall Be 0.10mm Total In Excess Of "b2" And "b4" Dimension At Maximum Material Condition.

単位 : mm

SYMBOL	DIMENSIONS			NOTES
	MIN.	NOM.	MAX.	
A	4.83	5.02	5.21	
A1	2.29	2.41	2.55	
A2	1.50	2.00	2.49	
b	1.12	1.20	1.33	
b1	1.12	1.20	1.28	
b2	1.91	2.00	2.39	6
b3	1.91	2.00	2.34	
c	0.55	0.60	0.69	6
c1	0.55	0.60	0.65	
D	20.80	20.95	21.10	4
D1	16.25	16.55	17.65	5
D2	0.51	1.19	1.35	
E	15.75	15.94	16.13	4
E1	13.46	14.02	14.16	5
E2	4.32	4.91	5.49	3
e	5.44BSC			
L	19.81	20.07	20.32	
L1	4.10	4.19	4.40	6
ØP	3.56	3.61	3.65	7
ØP1	7.19REF.			
Q	5.39	5.79	6.20	
S	6.04	6.17	6.30	

Note: The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC(RoHS2). RoHS Certification and other certifications can be obtained from GPT sales representatives or GPT website (then click “English” on the right top) : <http://globalpowertech.cn/>

GPT online store is now open! you can place an order directly online, buy it easily, and send it directly from the factory! For more detailed product, price information and coupon activities, please log in to GPT online store: <http://sc.globalpowertech.cn/>

More product datasheets and company information can be found in:
<https://www.globalpowertech.cn/>

