




Technical Specification



EIA WR	WR42
Frequency Range(GHz)	18.0 – 26.5
Bandwidth	Full
Isolation(dB)	20 Min.
Insertion Loss(dB)	0.5 Max.
VSWR	1.30:1 Max.
Flange	FBP220(UBR220) (Modified with 4xM3 Deep 4 threaded holes)
Forward Power(W)	50
Reverse Power(W)	15
Material	Al
Size(mm)	101 x 30 x 26.3
Net Weight(Kg)	0.10Around

Outline Drawing (Size: mm)




AINFO Inc.

Page 1 of 3

China(Beijing):
China(Chengdu):
USA :Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)



FBP220

AINFO Inc.

Page 2 of 3

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

Isolation & I.L. & VSWR

