


## 830nm 1W Uncooled Multimode Laser Diode Module

TY-830NM+/-10NM-1.0W-25C-2PIN-0.14NA-ST-50



SkyEra delivers TY-830NM+/-10NM-1.0W-25C-2PIN-0.14NA-ST-50 diode lasers employing professional coupling technology, that enjoy multiple advantages, e.g., compact design, stable output power, high power, high efficiency and convenient packaging. These laser diode modules can provide solutions for fiber laser applications and direct suppliers.

The performance and aging tests have been performed upon the production line to guarantee reliable, stable and long lifetime of products. To provide customers with high-quality, high cost performance products is the company's goal.

### Key Parameters:

- Based on single fire spot laser module
- High output power 1W
- High stability
- 0.14NA 50μm core multimode fiber
- Parallel weld 2-Pin sealed package
- Standard central wavelength 830nm
- RoHS compliance

### Application:

- Medical
- Printing
- Lighting
- Material processing


### Specification:

Functional parameters are tested on condition that the heat sink temperature is 25 degree, contact resistance of the component and the heat sink is smaller than 1CM<sup>2</sup> K/W.

Parameter	Min	Typ	Max	Unit	Conditions
Output Power	-	1	-	W	
Centre Wavelength					
TY830±10	820	830	840	nm	
TY830±5	825	830	835		
Spectral Width (FWHM)	-	3.5	6	nm	
Threshold Current	-	0.25	0.4	A	
Operating Current	-	1.2	1.4	A	
Operating Voltage	-	1.85	2.2	V	
Convention Efficiency	-	45	-	%	
>90% Power	-	0.12	-	NA	
Wavelength shift vs. Temperature	-	0.28	-	nm/°C	
Slop Efficiency	-	0.95	-	W/A	
Storage Temperature	-30	-	70	°C	Non-Condensing
Operating Temperature	15	-	55	°C	
Fiber Bend Radius	37.5	-	-	mm	
Buffer Diameter	-	250	-	μm	
Cladding Diameter	-	125	-	μm	
Core Diameter	-	50	-	μm	
Numeric Aperture	-	0.14	-	NA	
Fiber Connector	-	ST	-	-	

## 2. Dimension Diagram

Unit: MM



PIN OUT:

PIN	Description
A	LD+
B	LD-

## 3. Instructions

- Avoid eyes or skin exposure to direct or scattered radiation;
- ESD protection is required for transportation, storage and operation; short-circuit protection between pins is required for transportation and storage.
- Please connect pins by solder when operating current is over 6A; solder point should be close to the root of pins with a max soldering temperature at 260°C and a duration less than 10 seconds ;
- Drive constant current power supply by laser and avoid surge while working;
- Operate under rated current and rated power;
- Good heat dissipation is required;
- Operating temperature is 15°C~55°C;
- Storage temperature is -30°C~+70°C

