

Primary Lithium Battery

ER17505

3.6V Lithium-thionyl chloride[Li-SOCl₂]
 A-size bobbin cell



Benefits

- High and Stable Voltage
- Energy Density up to 590Wh/kg
- Long Shelf Life (2% Self-discharge Rate per Year)
- Wide Operating Temperature (-55°C~+85°C)

Key Features

- Stainless Steel Container
- Glass to metal hermetic sealing
- Non-flammable electrolyte
- CE, UL(MH10060) and UN38.3 Certified

Main Applications

- Security system
- Smart metering
- RFID / IoT system
- Wireless transmitting
- Smart home devices
- Military devices

Electrical Characteristics

Open circuit voltage (at 23±2°C) **3.65V**

Nominal capacity **3600mAh**

(At+25°C, battery discharged at continuous current 1.7mA until voltage reaches cut-off voltage 2.0V. The capacity can vary at different temperature, discharge current or cut-off voltage.)

Maximum continuous current **100mA**

(At+25°C, 2.0V cut-off, battery discharged for minimum 50% of nominal capacity.)

Maximum pulse discharge current **250mA**

(At+25°C, 2.0V cut-off, battery discharged for minimum 50% of nominal capacity with max pulse for 3 seconds after 27 seconds break. The discharged capacity may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions. Consult HCB.

Storage (recommended) **≤30°C**
(For more severe conditions, consult HCB) **≤75%RH**

Operating temperature range **-55°C~+85°C**

(Operation above ambient temperature may lead to reduced capacity and lower voltage readings at the beginning of pulses. Consult HCB)

HCB BATTERY CO., LTD

Add: Special No 1. Taizhong Avenue, Gaoqiao Industrial Park,
 Wujiashan Economic Development Zone, Wuhan, P.R.China

P.O.: 430040
 Tel: +86(0)27 83248452
 Fax: +86(0)27 83248455

Email: haocheng@cnhcb.com
 Web: www.cnhcb.com
 No.: HCB-MKT.PM-S[V1.0 2017 02]

Primary Lithium Battery

ER17505




3.6V Lithium-thionyl chloride[Li-SOCl₂]
A-size bobbin cell

Physical Characteristics

Diameter (max)	17.0mm
Height(max)	50.5mm
Typical weight	25.0g
Lithium metal content	0.93g

MSDS as per request
Diode(1N4007, 1N5819)
PTC(SRS175...)

Tag, wire, connector, etc. available




Dimensions in mm


WARNING:

- Do not short circuit
- Do not recharge
- Do not puncture
- Do not crush
- Do not dismantle
- Do not incinerate
- Do not mix new and used batteries
- Do not heat above 100°C


1. Typical discharge profiles at 23±2°C
(at the mid-discharge)



2. Voltage plateau versus Current and Temperature
(at the mid-discharge)



3. Storage characteristics



HCB BATTERY CO., LTD

Add: Special No 1. Taizhong Avenue, Gaoqiao Industrial Park,
Wujiashan Economic Development Zone, Wuhan, P.R.China

P.O.: 430040

Tel: +86 (0) 27 83248452

Fax: +86 (0) 27 83248455

Email: haocheng@cnhcb.com

Web: www.cnhcb.com

Version No.: HCB-MKT. PM-S[V1.0 2017 02]vzvzv