

TX-5060RGBW20FC120-NUVCNG-02AH80

PRODUCT SPECIFICATION

Features:

- ◆Excellent transiting heat from LED chip operating under R/B/G/W:IF=1.0A.
- ◆Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- ◆High luminous output.
- ◆No UV.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆ Red:AlInGaP
- ◆ Green: GaInN
- ◆ Blue:GaInN
- ◆ White:GaInN

Emitting Color:


- ◆Red (R)
- ◆Green (G)
- ◆Blue (B)
- ◆White (W)

Applications:

- ◆Auxiliary lighting
- ◆Ambient lighting
- ◆Architectural lighting
- ◆Entertainment lighting

Part No.	TX-5060RGBW20FC120-NUVCNG-02AH80	Spec No.	WKF-FC0030	Page	1 of 9
----------	----------------------------------	----------	------------	------	--------

Package Dimensions:



Notes:

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are ±0.1mm .

Absolute Maximum Ratings (Tc=25℃)

Parameter	Symbol		Ratings	Unit
Forward Current	IF	R	2.0	A
		G	1.5	
		B	1.5	
		W	1.8	
Reverse Voltage	VR		Not designed for reverse operation	V
Power Dissipation	PD	R	6.3	W
		G	6.5	
		B	5.4	
		W	6.7	
Junction Temperature	Tj	R	115	℃
		G	150	
		B	150	
		W	150	
Electrostatic Discharge Threshold (ESD)	ESD		2000	V
Storage Temperature	Tstg		-40~+70	℃
Operation Temperature	Topr		-30~+85	

Notes:

- Specifications are subject to change without notice.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:
STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Electrical Optical Characteristics (Tc=25°C, IF=1.0A)


Parameter	Symbol	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	Φ_v	R	95	—	110	lm
		G	180	—	220	
		B	30	—	40	
		W	235	—	265	
Forward Voltage	V_f	R	2.0	—	2.8	V
		G	3.0	—	3.6	
		B	3.0	—	3.6	
		W	3.0	—	3.6	
Dominant Wavelength	λ_d	R	615	620	625	nm
		G	522	527	532	
		B	447	452	457	
Peak-emission Wavelength	λ_p	R	625	630	635	nm
		G	516	521	526	
		B	442	447	452	
Correlated Colour Temperature	CCT	W	3780	—	4300	K
Color Rendering Index	Ra	W	—	80	—	—
Viewing Angle at 50 % IV	$2\theta_{1/2}$	—	—	120	—	Deg
			—	120	—	
Reverse Current	$V_R=5V$	R	—	—	2	μA
		G	—	—	2	
		B	—	—	2	
	—	W	Not designed for reverse operation			
Thermal Resistance Junction to Case	$R\theta_{J-C}$	—	—	0.8	—	K/W
Temperature Coefficient of Voltage	$V\Delta F/T$	R	—	-3.12	—	mV/°C
		G	—	-4.5	—	
		B	—	-2.52	—	
		W	—	-3.02	—	

Notes:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. Luminous flux measurement tolerance: $\pm 10\%$.
4. Forward voltage measurement tolerance: $\pm 3\%$.
5. Ra measurement tolerance: ± 2 .

Part No.	TX-5060RGBW20FC120-NUVCNG-02AH80	Spec No.	WKF-FC0030	Page	4 of 9
----------	----------------------------------	----------	------------	------	--------





White light Color coordinate filing Tc=25°C, IF=1.0A





Region	CCT Range		X1	Y1	X2	Y2	X3	Y3	X4	Y4
	Min	Max								
5C1	3780K	3950K	0.394	0.3944	0.3958	0.4001	0.3869	0.3951	0.3853	0.3892
5D2	3780K	3950K	0.3903	0.3825	0.394	0.3944	0.3853	0.3892	0.3823	0.3775
5B3	3950K	4150K	0.3849	0.3876	0.3866	0.3942	0.3775	0.3886	0.3759	0.3816
5B4	3950K	4150K	0.3813	0.3738	0.3849	0.3876	0.3759	0.3816	0.3732	0.369
5A2	4150K	4300K	0.3727	0.3667	0.3751	0.3778	0.3689	0.374	0.367	0.3634

Typical Electrical/Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)



Notes: — Red (R) ; — Green (G) ; — Blue (B) ; — White (W) ;



Notes: Red (R) ; Green (G) ; Blue (B) ; White (W) ;

Notes:

1. $2\theta_{1/2}$ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is $\pm 5^\circ$.

Usage Precautions


Storage Environment Condition

Temperature: 5°C ~ 30°C (41°F ~ 86°F)

Humidity: 60% RH Max.

Soldering Condition

Use the conditions shown to the under figure.





Profile Feature	Lead-Based Solder
Average Ramp-Up Rate (T_{Smax} to T_P)	3°C/second max.
Preheat: Temperature Min (T_{Smin})	100°C
Preheat: Temperature Max (T_{Smax})	150°C
Preheat: Time (T_{Smin} to T_{Smax})	60-120 seconds
Time Maintained Above: Temperature (T_L)	183°C
Time Maintained Above: Time (T_L)	60-150 seconds
Peak/Classification Temperature (T_P)	225°C
Time Within 5°C of Actual Peak Temperature (T_P)	10-30 seconds
Ramp-Down Rate	6°C/second max.
Time 25°C to Peak Temperature	6 minutes max.

Note:

All temperatures refer to topside of the package, measured on the package body surface.

Dimensions For Cannulation And Packaging

Quantity:500PCS

**Notes:**

1. All dimensions are in millimeters.
2. Tolerances are ± 2.0 mm unless otherwise noted.
3. The products are packaged together with silica gel, Transport, not to the weight of welding LED light-emitting area, As a result of the weight of LED light-emitting zone in the quality of, Irresponsible of the Company.