

SLD1550P-A2

Description

The SLD1550P-A2 is a 1550 nm, low-power, broadband Superluminescent Diode (SLD) with a near-Gaussian spectral profile and low ripple. This SLD is housed in a standard 14-pin butterfly package with FC/APC-connectorized, polarization-maintaining fiber. An integrated thermistor allows for temperature control, thus stabilizing the power and spectrum.

Specifications

CW; $T_{CHIP} = 25^{\circ}C$, $T_{CASE} = 0$ to $65^{\circ}C$


SLD1550P-A2				
	Symbol	Min	Typical	Max
Center Wavelength	λ_C	1520 nm	1550 nm	1580 nm
Operating Current	I_{OP}	-	550 mA	600 mA
ASE Power*	P_{ASE}	2.0mW	2.5 mW	-
Optical 3 dB Bandwidth*	BW	85 nm	90 nm	-
RMS Gain Ripple *	δG	-	-	0.25 dB
Forward Voltage*	V_F	-	1.6 V	2.0 V
TEC Operation (Typical / Max @ $T_{CASE} = 25^{\circ}C / 65^{\circ}C$)				
- TEC Current	I_{TEC}	-	0.35 A	1.5 A
- TEC Voltage	V_{TEC}	-	0.5 V	3.5 V
- Thermistor Resistance	R_{TH}	-	10 k Ω	-

*@ I_{OP}




Performance Plots


SLD1550P-A2 Optical Spectrum



SLD1550P-A2 LIV



Drawings



Note: Output isolator and monitor photodiode are available options for butterfly-packaged diodes. Please contact Technical Support for more information.