

Features

- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation


V_{RRM}	650V
$I_F (T_c = 158.5^\circ\text{C})$	6A
Q_c	20nC

Benefits


- Unipolar rectifier
- Substantially reduced switching losses
- No thermal run-away with parallel devices
- Reduced heat sink requirements

Applications

- SMPS, PFC
- Solar application, UPS, EV/HEV
- Motor drives, Wind turbine, Rail traction



DFN5x6



Inner Circuit



G = GPT
5 = Gen3
S = SiC Schottky Diode
65 = Voltage Rating 650V
06 = Current Rating 6A
Z = DFN5x6
DDDDDD = Traceable Code



Maximum Ratings (at $T_J = 25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	650	V
Surge Peak Reverse Voltage	V_{RSM}	650	V
Continuous Forward Current $T_c = 25^\circ\text{C}$ $T_c = 135^\circ\text{C}$ $T_c = 158.5^\circ\text{C}$	I_F	22.5 10.5 6	A
Repetitive Peak Forward Surge Current $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	I_{FRM}	30	A
Non-Repetitive Forward Surge Current $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	I_{FSM}	54	A
i^2t Value $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	$\int i^2 dt$	14.58	A^2s
Power Dissipation $T_c = 25^\circ\text{C}$ $T_c = 110^\circ\text{C}$	P_{tot}	88 38	W
Operating Junction Range	T_J	-55 to +175	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to +175	$^\circ\text{C}$

Electrical Characteristics (at $T_J = 25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
DC Blocking Voltage	V_{DC}		650	-	-	V
Forward Voltage	V_F	$I_F = 6\text{A}$				V
		$T_J = 25^\circ\text{C}$	-	1.32	1.5	
		$T_J = 175^\circ\text{C}$	-	1.6	1.8	
Reverse Current	I_R	$V_R = 650\text{V}$				μA
		$T_J = 25^\circ\text{C}$	-	0.12	50	
		$T_J = 175^\circ\text{C}$	-	0.91	100	
Total Capacitance	C	$f = 1\text{MHz}$				pF
		$V_R = 0\text{V}$	-	384	-	
		$V_R = 200\text{V}$	-	40.9	-	
		$V_R = 400\text{V}$	-	40.1	-	
Total Capacitive Charge	Q_C	$V_R = 400\text{V}$ $T_J = 25^\circ\text{C}$	-	20	-	nC
Capacitance Stored Energy	E_C	$V_R = 400\text{V}$	-	5	-	μJ

Thermal Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
Thermal Resistance, junction-case	$R_{th(j-c)}$		-	1.7	-	$^\circ\text{C/W}$

Typical Characteristics Curves




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Power Derating




Figure 4. Current Derating

Typical Characteristics Curves




Figure 5. Capacitance vs. Reverse Voltage




Figure 6. Reverse Charge vs. Reverse Voltage




Figure 7. Capacitance Stored Energy





Figure 8. Transient Thermal Impedance

Package Dimensions



Note:

1. All Dimensions are in mm.
2. Package body sizes exclude Mold Flash, Protrusion or Gate Burrs.
Mold Flash, Protrusion or Gate Burrs shall not exceed 0.10mm per side.
3. Package body sizes determined at the outermost extremes of the plastic.
Body exclusive of Mold Flash, Tie Bar, Tie Bar Burrs, Gate Burrs and Interlead Flash, but including any mismatch between the top and bottom of the plastic body.
4. The package top may be smaller than the package bottom.

Dimension	Millimeters		
	Min	NOM	Max
A	0.90	1.00	1.10
A1	0.00	-	0.05
b	0.33	0.41	0.51
c	0.20	0.25	0.30
D1	4.80	4.90	5.00
D2	3.61	3.81	3.98
E	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	2.66	2.76	2.88
e	1.27 BSC		
H	0.41	0.51	0.61
K	2.00	2.10	2.20
L	0.53	0.63	0.73
L1	0.06	0.13	0.20
L3	0.15	0.25	0.35
Q	4.12	4.22	4.32
α	0°	-	12°

Ordering Information

Part Number	Marking	Package	Packaging Mode
G5S6506Z	G5S6506Z	DFN5x6	4000/Reel

Notes

- Global Power Technology reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice.
- The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics.

Related Links

- Global Power Technology Website: <http://www.globalpowertech.cn/>
- GPT online store is now open! you can place an order directly online, buy it easily, and send it directly from the factory! For more detailed product, price information and coupon activities, please log in to GPT online store: <http://sc.globalpowertech.cn/>

