

2J6702Ba

2.4/5.0 GHz ISM MIMO Screw Mount

Key Features

Cable 1: 2.4/5.0 GHz ISM

- 2410-2490 MHz
- 4920-5925 MHz

Cable 2: 2.4/5.0 GHz ISM

- 2410-2490 MHz
- 4920-5925 MHz

Screw Mount

Anti-Rotation Mechanism


Ground Plane Dependent

Customizable Cable and Connector

Certificates: IP67, IP69K,

IK09 and IK10 version possible

Dimensions Ø 77.3 × 36.5 mm



1. Antenna and electrical specifications

Cable 1

Parameters	2.4/5.0 GHz ISM Antenna	
Standards	WiFi, BT, ZigBee, ISM	
Band (MHz)	2.4 GHz	5.0 GHz
Frequency (MHz)	2410-2490	4920-5925
Return Loss (dB)	~-12.4	~-13.4
VSWR	~1.7:1	~1.6:1
Efficiency (%)	~40.6	~21.8
Peak Gain (dBi)	~1.9	~1.6
Average Gain (dB)	~-3.9	~-6.7
Impedance (Ohm)	50	
Polarisation	Linear	
Radiation Pattern	Omni-Directional	
Max. Input Power (W)	10	
Connector Type	SMA-Male-RP Standard (Other Connectors Available)	
Cable Length	300 cm Standard (Any Cable Length Available)	
Cable Type	DACAR302 Standard (Other Cables Available)	

Cable 2

Parameters	2.4/5.0 GHz ISM Antenna	
Standards	WiFi, BT, ZigBee, ISM	
Band (MHz)	2.4 GHz	5.0 GHz
Frequency (MHz)	2410-2490	4920-5925
Return Loss (dB)	~-11.5	~-13.5
VSWR	~1.7:1	~1.6:1
Efficiency (%)	~40.9	~19.5
Peak Gain (dBi)	~1.8	~1.3
Average Gain (dB)	~-3.9	~-7.2
Impedance (Ohm)	50	
Polarisation	Linear	
Radiation Pattern	Omni-Directional	
Max. Input Power (W)	10	
Connector Type	SMA-Male-RP Standard (Other Connectors Available)	
Cable Length	300 cm Standard (Any Cable Length Available)	
Cable Type	DACAR302 Standard (Other Cables Available)	

Antenna Measurement Conditions:

Mounted on 30 x 30 cm Metal Plate

200 cm of DACAR302



Measured in Certified CTIA 3D Anechoic Chamber



2. Mechanical and environmental specifications


Specifications	2J6702Ba
Mounting Type	Screw Mount
Dimensions (mm)	Ø 77.3 × 36.5
Max. Tighten Torque (Nm)	6 Nm
Radome	ABS
Radome color	Black
Antenna Base	Zamak
Gasket	TPE
Operating Temperature (C)	-40 to +85
Storage Temperature (C)	-40 to +85
Substance Compliance	RoHS
Certificates	IP67, IP69K. IK09 and IK10 version possible with different material

3. Antenna parameters


Cable 1: 2.4/5.0 GHz ISM












Cable 2: 2.4/5.0 GHz ISM









ISOLATION FOR CABLE 1 AND 2




ENVELOPE CORRELATION COEFFICIENT FOR CABLE 1 AND 2






Radiation pattern reference

Cable 1: 2.4/5.0 GHz ISM







2450 and 5500 MHz Radiation pattern

Cable 2: 2.4/5.0 GHz ISM



2450 and 5500 MHz Radiation pattern

4. Antenna drawings



Note: Dimensions are in millimeters
***Dimensions are after mounting**
****Max. Torque= 6 Nm**

5. Antenna Images





Макро Групп – это:

- дистрибьютор электронных компонентов с 1994 года
- контрактный производитель электроники с 2007 года с собственным производством в Санкт-Петербурге (компания Макро ЕМС, входит в ГК Макро Групп)
- поставщик полупроводниковых материалов
- комплексный поставщик электронных компонентов
- моделирование и производство полупроводниковых эпитаксиальных гетероструктур для задач оптоэлектроники

Головной офис расположен в Санкт-Петербурге. Собственные представительства в крупных промышленных городах России и стран СНГ.

Преимущества для наших заказчиков:

- работа по тендерам с 2012 года
- оформление банковских гарантий
- отсрочки платежей
- поставка электронных компонентов по проектным ценам
- инженерная поддержка проектов заказчиков
- сертификат системы менеджмента качества ISO 9001-2015
- необходимые сертификаты и лицензии

Данный файл получен с сайта www.macrogroup.ru