



LEADTEK TFT DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	TPM P/N	LCM P/N	Product Category	Resolution	Viewing Angle	LCM A.A (mm)	LCM O.D (mm)	LCM Interface	LCM Luminance	Touch Screen	Structure	TPM V.A (mm)	TPM O.D (mm)	TP Interface	TPM Luminance	Operating Temp	Storage Temp
1.3"	Square		LTK013QVBLM02-V1	LCM	240*240	IPS	23.4*23.4	26.2*29.22*1.46	MCU/SPI	1000							-20~+60℃	-30~+70℃
1.54"	Square	LTK015QVHCT04-V3	LTK015QVHLM04-V1	LCM+CTP	240*240	IPS	27.72*27.72	30.92*33.72*2.58	SPI	350	CTP	GF	28.32*28.32	42.30*42.30*3.90	IIC	300	-10~+60℃	-20~+70℃
1.77"	Portrait		LTK018FTXLM13-V0	LCM	128*160	TN	28.03*35.04	34.30*44.76*2.45	SPI	400							-20~+70℃	-30~+80℃
2.0"	Portrait	LTK020QVHGT20-V0	LTK020QVHLM20-V0	LCM+CG	240*320	IPS	30.6*40.8	34.6*47.8*2.23	SPI	500	CG		31.4*41.6	44.82*78.18*3.55		440	-20~+70℃	-30~+70℃
2.1"	Circular		LTK021SQBLM14-V0	LCM	480*480	IPS	53.28*53.28	56.18*59.71*2.20	RGB	360							-20~+60℃	-30~+70℃
2.4"	Portrait	LTK024QVBGT20-V0	LTK024QVBLM20-V0	LCM+CG	240*320	IPS	36.72*48.96	40.92*57.45*2.46	SPI	300	CG		49.56*37.32	40.92*57.45*2.46		250	-20~+70℃	-30~+80℃
2.8"	Portrait		LTK028QVHLM05-V1	LCM	240*320	IPS	43.2*57.6	50*69.2*2.85	MCU	500							-20~+70℃	-30~+80℃
3.4"	Bar type	LTK034MNBT13-V0	LTK034MNBLM13-V0	LCM+CTP	180*640	IPS	23.22*82.56	25.72*88.83*1.58	MIPI	340	CTP	GG	23.72*83.16	29.72*92.83*3.61	IIC	300	-20~+70℃	-30~+80℃
3.4"	Circular	LTK034MNBT12-V0	LTK034MNBLM12-V0	LCM+CTP	800*800	IPS	87.60*87.60	94.90*96.95*2.24	MIPI	350	CTP	GF	88.60*88.60	109.20*113.47*3.77	IIC	300	-20~+70℃	-30~+80℃
3.5"	Landscape		LTK035QVBLM01-V2	LCM	320*240	IPS	70.08*52.56	76.90*63.90*3.20	RGB	320							-20~+70℃	-30~+80℃
3.5"	Portrait	LTK035HVCCT34-V0	LTK035HVCLM34-V0	LCM+CTP	320*480	TN	48.96*73.44	54.50*83*2.2	SPI	380	CTP	GG	49.66*74.14	69.50*116.50*4.17	IIC	320	-10~+60℃	-20~+70℃
3.5"	Portrait	LTK035P4046TX-09QC-V1	LTK035P4046TX-V0	LCM+CTP	320*480	IPS	48.96*73.44	54.48*84.71*2.30	MCU/SPI	400	CTP	GG	49.56*74.04	70.8*102.8*6.2	IIC	340	-20~+60℃	-30~+70℃
3.5"	Portrait		LTK035HVCLM36-V2	LCM	320*480	IPS	48.96*73.44	54.48*84.71*2.20	MCU	300							-20~+60℃	-30~+70℃
3.5"	Landscape		LTK035VGCLM40-V0	LCM	640*480	IPS	70.08*52.56	74.50*62.40*2.29	RGB	400							-20~+70℃	-30~+80℃
3.5"	Landscape	LTK035VGCCT40-V0	LTK035VGCLM40-V0	LCM+CTP	640*480	IPS	70.08*52.56	74.50*62.40*2.29	RGB	400	CTP	GG	70.68*53.16	76.60*63.60*3.67	IIC	340	-20~+70℃	-30~+80℃
3.51"	Bar type	LTK346HS4003B-G-V4	LTK346HS4003B-V4	LCM+CG	340*800	IPS	81.00*33.97	89*37.27*1.60	MIPI	330	CG		81*33.97	194.2*44.21*2.9		300	-20~+70℃	-30~+80℃
3.69"	Bar type	LTK037FTBCT11-V0	LTK037FTBLM11-V0	LCM+CTP	172*640	IPS	22.58*84.00	24.89*89.10*2.00	MIPI	350	CTP	GG	23.08*84.00	28.89*93.10*4.03	IIC	300	-20~+70℃	-30~+80℃
3.9"	Bar type	LTK039MNBT11-V0	LTK039MNBLM11-V0	LCM+CTP	480*128	IPS	95.04*25.34	103.20*34.85*2.50	RGB	500	CTP	GG	95.64*25.94	113.20*40.85*4.15	IIC	420	-20~+70℃	-30~+80℃
3.95"	Square	LTK040H5025C-CTP-B-TDM-V2	LTK040FTHLM49-V0	LCM+CTP	480*480	IPS	71.86*70.18	74.83*78.98*1.98	RGB	350	CTP	GFF	68.00*68.00	84.80*84.80*3.55	IIC	280	-20~+70℃	-30~+80℃
3.97"	Portrait	LTK040WVBCT13-V0	LTK040WVBLM13-V0	LCM+CTP	480*800	TN	51.84*86.40	57.14*96.85*2.00	MIPI	350	CTP	GFF	52.64*87.20	67.51*110.55*3.70	IIC	300	-10~+60℃	-20~+70℃
3.97"	Portrait		LTK040WVBLM10-V0	LCM	480*800	IPS	51.84*86.40	56.34*95.70*2.00	MIPI	350							-20~+70℃	-30~+80℃
3.99"	Bar type	LTK040MNBT24-V0	LTK040MNBLM24-V0	LCM+CTP	400*960	IPS	39.18*94.03	42.90*102.08*2.19	MIPI	480	CTP	GG	39.78*94.63	45.90*105.08*4.20	IIC	410	-20~+70℃	-30~+80℃
4.0"	Circular	LTK040MNBT18-V0	LTK040MNBLM18-V0	LCM+CTP	720*720	IPS	101.52*101.52	105.60*109.87*2.20	MIPI	470	CTP	GFF	102.12*102.12	109.21*113.47*3.73	IIC	400	-20~+70℃	-30~+80℃
4.3"	Landscape		LTK043WQHLM01-V0	LCM	480*272	IPS	95.04*53.86	105.50*67.20*2.90	SPI	600							-10~+60℃	-20~+70℃
4.3"	Landscape	LTK430WQ12B-T-V0	LTK430WQ12B-V0	LCM+RTP	480*272	IPS	95.04*53.86	105.50*67.20*3.00	RGB	600	RTP	PG	99.30*57.60	104.80*65.00*4.15	4L	450	-20~+70℃	-30~+80℃
4.3"	Portrait	LTK043WVBCT28-V0	LTK043WVBLM28-V0	LCM+CTP	480*800	IPS	56.16*93.60	60.00*101.80*1.70	RGB	1100	CTP	GG	56.76*94.20	78.86*121.90*3.73	IIC	1000	-20~+70℃	-30~+80℃
4.3"	Portrait		LTK043WVBLM11-V0	LCM	480*800	IPS	56.16*93.65	60.00*101.80*1.70	RGB	450							-20~+70℃	-30~+80℃
4.3"	Portrait	LTK430WV15A-CT-V4	LTK430WV15A-V4	LCM+CTP	480*800	IPS	56.16*93.60	60.00*101.80*1.70	MIPI	280	CTP	GFF	56.66*94.10	66.26*113.90*3.00	IIC	230	-20~+60℃	-30~+80℃



LEADTEK TFT DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	TPM P/N	LCM P/N	Product Category	Resolution	Viewing Angle	LCM A.A (mm)	LCM O.D (mm)	LCM Interface	LCM Luminance	Touch Screen	Structure	TPM V.A (mm)	TPM O.D (mm)	TP Interface	TPM Luminance	Operating Temp	Storage Temp
7.0"	Bar type		LTK070MNHLM34-V0	LCM	280*1424	IPS	33.60*170.88	38.20*181.47*3.40	MIPI	450							-20~+70°C	-30~+80°C
7.84"	Portrait	LTK078WXBCT02-V0	LTK078WXBLM02-V0	LCM	400*1280	IPS	59.40*190.08	67.80*206.18*4.66	MIPI	500	CTP	GG	60.00*190.68	71.40*216.68*7.19	IIC	400	-20~+70°C	-30~+80°C
8.0"	Portrait	LTK080FTBCT25-V0	LTK080FTBLM25-V0	LCM+CTP	1200*1920	IPS	107.64*172.22	114.60*184.10*2.80	MIPI	600	CTP	GFF	108.64*173.22	132.60*193.60*4.30	IIC	520	-0~+50°C	-10~+60°C
8.0"	Landscape		LTK080FTCLM28-V0	LCM	1024*600	TN	176.64*99.36	192.80*116.90*6.40	LVDS	600							-20~+70°C	-30~+80°C
8.0"	Landscape	LTK080FTNCT29-V0	LTK080FTNLM29-V0	LCM	1024*768	IPS	162.05*121.54	174.00*136.00*2.45	LVDS	300	CTP		163.05*122.54	187.05*148.54*4.65	USB	250	-10~+50°C	-20~+60°C
8.0"	Portrait	LTK080P3138BL-Q-V3	LTK080WXBLM15-V0	LCM+CTP	800*1280	IPS	107.64*172.22	114.70*184.20*2.51	MIPI	420	CTP	GG	108.24*172.82	117.70*204.80*5.41	IIC	350	-20~+60°C	-30~+70°C
8.0"	Landscape		LTK080FTCLM27-V0	LCM	800*480	TN	176.64*99.36	192.80*116.90*6.40	RGB	650							-20~+70°C	-30~+80°C
8.8"	Bar type	LTK088MNHCT03-V0	LTK088MNHLM03-V0	LCM+CTP	1280*480	IPS	209.28*78.48	229.60*97.35*3.50	LVDS	1100	CTP	GG	209.88*79.08	239.60*107.35*5.55	IIC	1000	-20~+70°C	-30~+70°C
9.0"	Landscape		LTK090FTBLM12-V0	LCM	800*480	TN	198.00*111.70	210.70*126.50*5.00	RGB	400							-10~+50°C	-20~+60°C
9.7"	Landscape	LTK097FTICT10-V0	LTK097FTILM10-V0	LCM	1024*600	IPS	196.61*147.46	210.20*164.25*2.80	LVDS	350	CTP	GG	197.21*148.06	225.21*179.48*4.85	IIC		-10~+60°C	-20~+70°C
10.1"	Landscape	LTK101H5029W-08KC-V0	LTK101H5029W-V0	LCM+CTP	1024*600	TN	222.72*125.28	235.00*143.00*3.15	RGB	220	CTP	GG	223.30*125.80	267.40*162.50*5.10	IIC	170	-20~+50°C	-30~+60°C
10.1"	Portrait	LTK101WX08Q-QC-V3	LTK101WX08Q-V2	LCM+CTP	800*1280	IPS	135.36*216.58	143.00*228.60*2.75	MIPI	500	CTP	GFF	134.16*215.38	174.50*251.00*4.10	IIC	420	-20~+60°C	-30~+70°C
10.1"	Landscape	LTK101FTBCT50-V0	LTK101FTBLM50-V0	LCM+CTP	1280*800	IPS	216.96*135.60	229.26*149.08*2.6	LVDS	300	CTP	GG	215.70*134.40	248.00*165.00*4.80	IIC	250	-0~+50°C	-20~+60°C
10.1"	Portrait	LTK101FHNCT19-V0	LTK101FHNLM19-V0	LCM+CTP	1200*1920	IPS	135.36*216.57	143.00*228.60*2.65	MIPI	350	CTP	GG	135.96*217.17	146.80*239.37*4.23	IIC	300	-20~+60°C	-30~+70°C
10.1"	Portrait	LTK101FHNCT16-V1	LTK101FHNLM16-V1	LCM+CTP	1200*1920	IPS	135.36*216.57	143.00*228.60*2.65	MIPI	600	CTP	GG	135.96*217.17	146.80*239.37*4.23	IIC	520	-20~+60°C	-30~+70°C
10.1"	Landscape	LTK101WUBCT42-V0	LTK101WUBLM20-V0	LCM+CTP	1920*1200	IPS	216.81*135.50	229.46*149.10*4.40	LVDS	1000	CTP	GG	217.56*136.20	257.06*170.20*6.50	USB	800	-20~+70°C	-30~+80°C
10.1"	Landscape	LTK101WUBCT20-V0	LTK101WUBLM20-V0	LCM+CTP	1920*1200	IPS	216.81*135.50	229.46*149.10*4.40	LVDS	1000	CTP	GG	217.58*136.36	253.58*172.08*6.75	IIC	800	-20~+70°C	-30~+80°C
11.6"	Landscape		LTK116FHBLM01-V0	LCM	1920*1080	IPS	256.32*144.18	270.37*159.79*2.70	EDP	360							-10~+50°C	-20~+60°C
12.1"	Landscape	LTK121WXBCT13-V0	LTK121WXBLM13-V0	LCM+CTP	1280*800	IPS	261.12*163.20	278.00*184.00*6.63	LVDS	750	CTP	GG	262.20*164.20	301.90*203.90*9.73	USB	600	-20~+70°C	-30~+80°C
12.3"	Bar type	LTK123FHHCT14-V0	LTK123FHHLM14-V0	LCM+CTP	720*1920	IPS	109.51*292.03	124.20*303.13*6.05	MIPI	500	CTP	GG	110.31*292.83	146.00*335.50*9.15	IIC	420	-20~+70°C	-30~+80°C
15.0"	Landscape	LTK150FTFCT17-V0	LTK150FTFLM17-V0	LCM+CTP	1024*768	IPS	304.128*228.096	326.50*253.50*8.70	LVDS	850	CTP	GG	302.4*226.9	335.50*146.00*12.3	IIC+USB	750	-20~+70°C	-30~+80°C
15.6"	Landscape		LTK156FHBLM01-V0	LCM	1920*1080	IPS	344.16*193.59	350.66*205.25*3.20	eDP	250							-0~+50°C	-20~+60°C
15.6"	Landscape	LTK156FTBCT27-V0	LTK156FTBLM25-V0	LCM+CTP	1920*1080	IPS	344.16*193.59	360.00*212.30*6.30	eDP	750	CTP	GG	344.23*193.54	386.80*236.07*9.40	IIC+USB	600	-20~+70°C	-30~+80°C
18.5"	Landscape	LTK185FHBCT12-V1	LTK185FHBLM12-V1	LCM+CTP	1920*1080	IPS	408.96*230.04	430.37*254.60*9.30	LVDS	320	CTP	GG	408.70*229.00	477.00*297.30*13.65	IIC	270	-0~+60°C	-10~+60°C
21.5"	Landscape		LTK215FHBLM13-V0	LCM	1920*1080	IPS	478.66*260.28	495.64*292.21*9.90	LVDS	750							-0~+50°C	-10~+60°C
21.5"	Landscape		LTK215FHBLM02-V0	LCM	1920*1080	IPS	476.06*267.79	495.60*292.20*11.50	LVDS	400							-10~+50°C	-20~+60°C
21.5"	Landscape		LTK215S3015W-V0	LCM	1920*1080	IPS	478.66*260.28	495.64*292.21*8.90	LVDS	300							-10~+50°C	-20~+60°C
23.8"	Landscape		LTK238FTHLM13-V0	LCM	1920*1080	IPS	527.04*296.46	543.00*316.72*8.30	LVDS	250							-10~+50°C	-20~+60°C



LEADTEK TFT DISPLAY PRODUCT LIST



МАКРО
ГРУПП

Официальный дистрибьютор Leadtek
www.macrogroupp.ru displays@macrogroupp.ru

Size	Shape	TPM P/N	LCM P/N	Product Category	Resolution	Viewing Angle	LCM A.A (mm)	LCM O.D (mm)	LCM Interface	LCM Luminance	Touch Screen	Structure	TPM V.A (mm)	TPM O.D (mm)	TP Interface	TPM Luminance	Operating Temp	Storage Temp	
27.0"	Landscape		LTK270FTALM10-V0	LCM	1920*1080	IPS	597.89*336.31	607.10*354.10*13.93	LVDS	500							-0~+50°C	-20~+60°C	
31.5"	Landscape		LTK315FHOLM12-V0	LCM	1920*1080	IPS	698.40*392.85	722.2*422.30*15.50	LVDS	320								-10~+50°C	-20~+60°C



LEADTEK RUGGED DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	TPM P/N	LCM P/N	Product Category	Resolution	Viewing Angle	LCM A.A (mm)	LCM O.D (mm)	LCM Interface	LCM Luminance	Touch Screen	Structure	TPM V.A (mm)	TPM O.D (mm)	TP Interface	TPM Luminance	Operating Temp	Storage Temp
3.54"	Circular		LTK035VGHLM19-V0	LCM	800*640	IPS	90.00*72.00	97.60*83.79*4.04	RGB	1050							-30~+85℃	-40~+85℃
3.95"	Square	LTK040WVHCT29-V1	LTK040WVHLM02-V0	LCM+CTP	480*480	IPS	71.86*70.18	77.36*80.28*2.84	MIPI	1100	CTP	GFF	72.00*70.20	87.00*97.00*4.40	IIC	900	-20~+85℃	-30~+85℃
6.8"	Landscape	LTK068WSBCT10-V0	LTK068WSBLM10-V0	LCM+CTP	1024*600	IPS	151.76*79.80	160.20*90.30*4.56	LVDS	850	CTP	GG	152.36*80.40	175.56*107.60*7.51	IIC	800	-30~+80℃	-30~+80℃
7,00"	Landscape	LTK070FTNCT67-V0	LTK070FTNLM67-V0	LCM+CTP	1024*600	IPS	154.21*85.92	165.00*100.00*5.65	MIPI	1000	CTP	GG	154.48*86.32	165.00*100.00*7.60	IIC	850	-30~+80℃	-30~+80℃
8,00"	Landscape		LTK080FHBLM17-V0	LCM	1920*1200	IPS	172.20*107.60	181.70*119.70*5.50	LVDS	1000							-30~+85℃	-30~+85℃
8.88"	Bar type	LTK088FHHCT01-V0	LTK088FHLM01-V0	LCM+CTP	480*1920	IPS	54.72*218.88	64.10*231.20*4.60	MIPI	1000	CTP	GG	55.72*219.88	76.00*243.10*6.75	IIC	950	-30~+85℃	-40~+90℃
10.1"	Landscape	LTK101FTNCT54-V0	LTK101FTNLM54-V0	LCM+CTP	1024*600	IPS	222.72*125.28	235.00*143.00*5.20	LVDS	850	CTP	GG	223.72*126.28	257.00*159.60*7.50	IIC	750	-30~+85℃	-30~+85℃
10.25"	Bar type		LTK103FTALM15-V0	LCM	1920*720	IPS	243.65*91.37	254.71*107.05*6.00	LVDS	1000							-30~+75℃	-40~+85℃
10.4"	Landscape	LTK104XGHCT14-V0	LTK104XGHLM14-V0	LCM+CTP	1024*768	IPS	211.20*158.40	230.00*173.00*9.56	LVDS	800	CTP	GG	211.0*158.4	248.60*192.00*12.36	IIC+USB	680	-30~+85℃	-30~+85℃
10.4"	Landscape	LTK104XGNCT17-V0	LTK104XGNLM17-V0	LCM+CTP	1024*768	IPS	210.43*157.82	234.65*173.10*8.72	LVDS	1000	CTP	GG	211.10*158.40	239.20*179.40*11.82	IIC+USB	850	-30~+80℃	-30~+80℃
12.1"	Landscape	LTK121XGHCT15-V0	LTK121XGHLM15-V0	LCM+CTP	1024*768	IPS	245.76*184.32	260.50*204.00*7.45	LVDS	800	CTP	GG	246.0*184.5	289.30*227.50*10.25	IIC+USB	680	-30~+85℃	-30~+85℃
12.3"	Bar type	LTK123FHCGT17-V2	LTK123FHCLM17-V2	LCM+CG	1920*720	IPS	292.03*109.51	302.06*125.46*6.56	LVDS	1200	CG		292.83*110.31	335.50*146.00*8.89		1000	-30~+85℃	-40~+90℃



LEADTEK TRANSFLECTIVE / REFLECTIVE DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	TPM P/N	LCM P/N	Resolution	Display Type	Color	Reflectivity	Power Consumption (mW)	LCM A.A (mm)	LCM O.D (mm)	Viewing Angle	LCM Interface	LCM Luminance	Touch Screen	Structure	TPM V.A (mm)	TPM O.D (mm)	TP Interface	TPM Luminance	Operating Temp	Storage Temp		
1.5"	Square		LTK015MNHLM15-V0	200*200	Reflective	B/W, 2 color	50,00%	0,045	27.66*27.66	29.46*31.71*0.72	60/60/60/60	SPI								-20~+70°C	-30~+80°C		
2.13"	Bar type		LTK021MNHLM11-V0	122*250	Reflective	B/W, 2 color	50,00%	0,07	23.668*48.5	27.10*56.20*0.80	60/60/60/60	MCU/SPI									-20~+70°C	-30~+80°C	
2.41"	Portrait		LTK024QVHLM17-V2	240*320	Transflective	16.7M, full color	25,00%	37,100	36.72*48.96	42.72*60.26*2.20	60/60/60/60	SPI	180								-20~+70°C	-30~+80°C	
2.8"	Portrait	LTK028BFBCT19-V0	LTK028BFBLM19-V0	240*320	Transflective	16.7M, full color	7,50%	120,00	43.20*57.60	50.00*69.20*2.57	60/60/60/60	SPI	55	CTP	G+F	43.80*58.20	56*80*3.69	IIC	45	-20~+70°C	-30~+80°C		
2.9"	Bar type		LTK029MNHLM11-V0	168*384	Reflective	B/W, 2 color	50,00%	0,060	29.10*66.85	36.60*70.95*1.50	60/60/60/60	SPI									-20~+70°C	-30~+80°C	
2.9"	Bar type		LTK029MNHLM12-V0	168*384	Reflective	R/B/W, 3 color	30,00%	0,13	29.10*66.85	36.60*70.95*1.50	60/60/60/60	SPI									-20~+70°C	-30~+80°C	
3.5"	Portrait	LTK035BFBCT48-V0	LTK035BFBLM48-V0	480*640	Transflective	16.7M, full color	9,50%	480,000	51.84*69.12	59.04*80.72*3.33	6'clock	MIPI	135	CTP	G+FF	52.44*69.72	65.04*86.69*4.63	IIC	110	-20~+70°C	-30~+80°C		
3.97"	Portrait	LTK040BFBCT45-V0	LTK040BFBLM45-V0	480*800	Transflective	16.7M, full color	9,50%	480,00	51.84*86.40	56.34*95.70*2.37	6'clock	MIPI	135	CTP	G+FF	52.44*87.00	62.70*102.90*3.70	IIC	110	-20~+70°C	-30~+80°C		
4.2"	Portrait		LTK042MNHLM14-V0	300*400	Reflective	B/W, 2 color	50,00%	0,100	63.6*84.8	67.60*91.00*1.50	60/60/60/60	SPI									-20~+70°C	-30~+80°C	
4.2"	Portrait		LTK042MNHLM15-V0	300*400	Reflective	R/B/W, 3 color	30,00%	0,20	63.6*84.8	67.60*91.00*1.50	60/60/60/60	SPI										-20~+70°C	-30~+80°C
5.0"	Landscape	LTK050VWHCT20-V1	LTK050VWHLM20-V1	800*480	Transflective	16.7M, full color	12,50%	1080,000	108.0*64.8	120.90*76.00*3.21	60/60/55/55	RGB	100	CTP	G+G	108.60*65.40	143.60*95.70*5.11	IIC	80	-20~+70°C	-30~+80°C		
5.0"	Landscape	LTK050PDBCT30-V0	LTK050PDBLM30-V0	800*480	Transflective	16.7M, full color	5,00%	1080,00	108.00*64.80	120.80*75.80*2.85	50/60/60/60	RGB	200	CTP	G+G	109.30*65.80	128.20*84.80*4.82	IIC	170	-30~+80°C	-30~+80°C		
5.46"	Portrait	LTK055HDHCT15-V0	LTK055HDHLM15-V0	720*1280	Reflective	16.7M, full color	23,00%	217,000	68.04*120.96	70.64*126.44*0.72	60/60/60/60	MIPI		CTP	G+FF	68.54*121.46	86.60*139.52*2.42	IIC		-20~+70°C	-30~+80°C		
5.6"	Portrait	LTK056PDHCT10-V0	LTK056PDHLM10-V0	720*1440	Transflective	16.7M, full color	10,00%	850,00	60.48*120.96	64.22*130.48*1.62	60/60/60/60	MIPI	80	CTP	G+G	61.08*121.56	70.24*136.51*3.65	IIC	70	-20~+70°C	-30~+80°C		
7.8"	Portrait	LTK078QFHCT16-V0	LTK078QFHLM16-V0	768*1024	Reflective	16.7M, full color	18,88%	358,000	118.89*158.52	123.03*165.22*0.72	60/60/60/60	MIPI		CTP	G+FF	119.49*159.12	138.49*180.02*2.55	IIC		-20~+60°C	-30~+70°C		
10.0"	Portrait		LTK100UXHLM10-V0	1200*1600	Reflective	16.7M, full color	25,00%	610,00	152.45*203.28	166.36* 211.88*2.01	60/60/60/60	MIPI									-20~+70°C	-30~+80°C	
10.13"	Portrait	LTK101QFHCT59-V0	LTK101QFHLM59-V0	1440*1920	Reflective	B/W, 2 color	43,05%	600,000	154.37*205.82	158.27*212.43*0.80	60/60/60/60	MIPI		CTP	G+FF	155.17*206.62	178.37*229.82*3.22	IIC		-20~+60°C	-30~+70°C		
15.6"	Landscape	LTK156PDHCT24-V0	LTK156PDHLM24-V0	1920*1080	Transflective	16.7M, full color	13,98%	7800,00	344.16*193.59	363.80*215.90*10.00	60/60/60/60	EDP	45	CTP	G+G	344.23*193.54	386.80*236.07*12.5	USB	35	-10~+50°C	-20~+60°C		
21.5"	Landscape	LTK215FHHCT15-V0	LTK215FHHLM15-V0	1920*1080	Transflective	16.7M, full color	11,00%	12960,000	476.64*268.11	495.60*292.20*9.00	60/60/60/60	LVDS	200	CTP	G+G	477.00*268.50	520.42*312.17*12.25	USB	150	-10~+50°C	-20~+60°C		
23.8"	Landscape		LTK238PDHLM11-V0	1920*1080	Reflective	16.7M, full color	19,64%	1905,00	527.04*296.46	532.54*302.86*1.30	60/60/60/60	LVDS									-20~+60°C	-30~+70°C	
28.0"	Landscape		LTK280PDHLM10-V0	3840*2160	Reflective	16.7M, full color	17,70%	4848,000	620.93*341.28	631.93*348.78*1.31	60/60/60/60	EDP										-20~+60°C	-30~+70°C



LEADTEK SMART DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	P/N	Display Resolution	Board Type	Display Interface	Signal Input	PCB Outline	Operating Temp	Storage Temp	Power	Touch Screen
2.4"	Bar type	LTK024QVHUM17-V2	240*320	UART	SPI	UART TTL	48.00*46.00	-20~+70°C	-30~+80°C	5V/2A	
2.9"	Bar type	LTK029MNHUM11-V0	168*384	UART	SPI	UART TTL	48.00*46.00	-20~+70°C	-30~+80°C	5V/2A	
3.4"	Bar type	LTK034MNBUT13-V0	180*640	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
3.4"	Circular	LTK034MNBUT12-V0	800*800	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
3.5"	Landscape	LTK035QVBAM01-V2	320*240	Signal transfer	RGB	AV	76.0*60.0*10.0	-20~+70°C	-30~+80°C	12V/3A	
3.5"	Circular	LTK035VGHUM19-V0	800*640	UART	RGB	UART TTL&232&485	56.00*66.00	-30~+85°C	-40~+85°C	5V/2A	
3.7"	Bar type	LTK037FTBUT11-V0	172*640	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
3.9"	Bar type	LTK039MNBUT11-V0	480*128	UART	RGB	UART TTL&232&485	56.00*66.00	-20~+70°C	-30~+80°C	5V/2A	CTP
4.0"	Portrait	LTK040MNBUT24-V0	400*960	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
4.2"	Portrait	LTK042MNHUM14-V0	300*400	UART	SPI	UART TTL	48.00*46.00	-20~+70°C	-30~+80°C	5V/2A	
4.3"	Landscape	LTK043VWHMT12-V1	800*480	Signal transfer	RGB	HDMI	76.7*63.7*8.0	-10~+60°C	-20~+70°C	12V/3A	CTP
4.3"	Landscape	LTK043VWHUT31-V0	800*480	UART	RGB	UART TTL&232&485	121.9*74.66*10.6	-10~+60°C	-20~+70°C	5V/2A	CTP
5.0"	Landscape	LTK050VVBUT18-V1	800*480	UART	RGB	UART TTL	158.70*100.0*15.0	-20~+70°C	-30~+80°C	5V/2A	CTP
5.0"	Landscape	LTK050VWHUM20-V0	800*480	UART	RGB	UART TTL&232&485	56.00*66.00	-20~+70°C	-30~+80°C	5V/2A	
5.0"	Landscape	LTK050VVBHT17-V0	800*480	Signal transfer	RGB	HDMI	150.0*100.0*10.0	-25~+70°C	-30~+80°C	3.3V/5V	CTP
5.0"	Portrait	LTK050HHDHUT13-V0	720*1280	UART	RGB	UART TTL&232&485	56.00*66.00	-10~+60°C	-20~+70°C	5V/2A	CTP
5.0"	Portrait	LTK050FTHHT29-V0	720*1280	Signal transfer	MIPI	HDMI	51.0*37.0*3.0	-20~+70°C	-30~+80°C	12V/3A	CTP
5.5"	Portrait	LTK055HHDHUM15-V0	720*1280	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	
5.6"	Portrait	LTK056PDHUT10-V0	720*1440	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
6.2"	Portrait	LTK062MNBUT10-V0	360*960	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
6.8"	Landscape	LTK068WSBHT10-V0	1024*600	Signal transfer	LVDS	HDMI	150.0*100.0*10.0	-30~+80°C	-30~+80°C	12V/3A	CTP
6.9"	Bar type	LTK069MNBUT12-V0	720*1440	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
7.0"	Bar type	LTK070MNHUT34-V0	280*1424	UART	MIPI	UART TTL&232&485	130.00*80.00	-20~+70°C	-30~+80°C	5V/2A	CTP
7.0"	Landscape	LTK070WV50CYW-CT-V0	800*480	Signal transfer	RGB	MCU	99.2*58.9*1.2	-10~+60°C	-20~+70°C	3.3V/5V	CTP
7.0"	Landscape	LTK070WV50CYW-02KC-HT-V0	800*480	Signal transfer	RGB	HDMI	90.0*62.0*15.0	-10~+60°C	-20~+70°C	12V/2A	CTP
7.0"	Landscape	LTK070WSHZT41-V0	1024*600	Signal transfer	RGB	MCU+SPI	98.0*65.8*1.0	-20~+60°C	-30~+70°C	3.3V/5V	CTP
7.0"	Landscape	LTK070WSHHT24-V0	1024*600	Signal transfer	LVDS	HDMI	90.0*62.0*15.0	-20~+70°C	-30~+80°C	12V/3A	CTP
7.0"	Landscape	LTK070WSHUT29-V0	1024*600	UART	RGB	UART TTL&232&485	158.70*100.0*15.0	-20~+60°C	-30~+70°C	5V/2A	CTP



LEADTEK SMART DISPLAY PRODUCT LIST



Официальный дистрибьютор Leadtek
www.macrogroup.ru displays@macrogroup.ru

Size	Shape	P/N	Display Resolution	Board Type	Display Interface	Signal Input	PCB Outline	Operating Temp	Storage Temp	Power	Touch Screen
8.0"	Portrait	LTK080FTBHT25-V0	1200*1920	Signal transfer	MIPI	HDMI	75.22*46.8*10.6	-0~+50℃	-10~+60℃	12V/3A	CTP
8.8"	Bar type	LTK088MNHHT03-V0	1280*480	Signal transfer	LVDS	HDMI	150.0*100.0*10.0	-20~+70℃	-30~+70℃	12V/3A	CTP
10.1"	Landscape	LTK101FTBHT50-V0	1280*800	Signal transfer	LVDS	HDMI	85.0*54.0*14.0	-0~+50℃	-20~+60℃	12V/3A	CTP
10.1"	Landscape	LTK101WUBLM20-HT-V0	1920*1200	Signal transfer	LVDS	HDMI	85.0*54.0*14.0	-20~+70℃	-30~+80℃	12V/3A	
10.4"	Landscape	LTK104XGHUT14-V0	1024*768	UART	LVDS	UART TTL&232&485	245.00*196.00	-30~+85℃	-30~+85℃	12V/2A	CTP
11.6"	Landscape	LTK116FHBHT01-V0	1920*1080	Signal transfer	eDP	HDMI	150.0*80.0*1.6	-10~+50℃	-20~+60℃	12V/3A	CTP
12.1"	Landscape	LTK121XGHUT15-V0	1024*768	UART	LVDS	UART TTL&232&485	280.00*224.00	-30~+85℃	-30~+85℃	12V/2A	CTP
13.3"	Landscape	LTK133FHBHT19-V0	1920*1080	Signal transfer	eDP	HDMI	150.0*80.0*1.6	-10~+50℃	-20~+60℃	12V/3A	CTP
15.0"	Landscape	LTK150TFUT17-V0	1024*768	UART	LVDS	UART TTL&232&485	346.00*273.00	-20~+70℃	-30~+80℃	12V/2A	CTP
15.6"	Landscape	LTK156FHBHT01-V0	1920*1080	Signal transfer	eDP	HDMI	150.0*80.0*1.6	-0~+50℃	-20~+60℃	12V/3A	CTP
19.0"	Landscape	LTK190L3027T-HT01-V1	1280*1024	Signal transfer	LVDS	HDMI	90.0*62.0*15.0	-0~+50℃	-20~+60℃	12V/3A	CTP