


SNTUNS50

SNTUN S 50 F 05 - ☐

① ② ③ ④ ⑤ ⑥



Recommended EMI/EMC Filter
NAC-04-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* The EMI/EMC Filter is recommended to connect with several devices.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal Input
- ⑤ Output voltage
- ⑥ Optional
- C : with Coating
- J : Connector type

MODEL	SNTUNS50F05	SNTUNS50F12	SNTUNS50F24
MAX OUTPUT WATTAGE[W]	50.0	50.4	50.4
DC OUTPUT	5V 10A	12V 4.2A	24V 2.1A

SPECIFICATIONS

	MODEL	SNTUNS50F05	SNTUNS50F12	SNTUNS50F24
INPUT	VOLTAGE[V]	AC85 - 264 1 ϕ (Please refer to the instruction manual 1.1 and 3.2)		
	CURRENT[A]	ACIN 100V 0.67typ (Io=100%)		
		ACIN 200V 0.37typ (Io=100%)		
	FREQUENCY[Hz]	50/60 (47 - 63)		
	EFFICIENCY[%]	ACIN 100V 76typ	80typ	81typ
		ACIN 200V 78typ	83typ	84typ
	POWER FACTOR (Io=100%)	ACIN 100V 0.95typ		
		ACIN 200V 0.90typ		
OUTPUT	INRUSH CURRENT[A]	ACIN 100V 15typ (Io=100%) (At cold start) (Ta=25°C)		
		ACIN 200V 30typ (Io=100%) (At cold start) (Ta=25°C)		
	LEAKAGE CURRENT[mA]	0.4/0.75 (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN)		
	VOLTAGE[V]	5	12	24
	CURRENT[A]	10	4.2	2.1
	LINE REGULATION[mV]	10max	24max	48max
	LOAD REGULATION[mV]	150max	100max	100max
	RIPPLE[mVp-p]	0 to +95°C *1 80max	120max	120max
		-20 to 0°C *1 140max	160max	160max
		0 to 15% Load *1 200max	280max	380max
PROTECTION CIRCUIT AND OTHERS	RIPPLE NOISE[mVp-p]	0 to +95°C *1 120max	150max	150max
		-20 to 0°C *1 200max	200max	250max
		0 to 15% Load *1 280max	360max	460max
	TEMPERATURE REGULATION[mV]	0 to +65°C 50max	120max	240max
		-20 to +95°C 100max	240max	480max
	DRIFT[mV]	*2 20max	40max	90max
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.50 - 5.50	10.80 - 13.20	21.60 - 26.40
	OUTPUT VOLTAGE SETTING[V]	5.00 - 5.15	12.00 - 12.48	24.00 - 24.96
	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
	OVERVOLTAGE PROTECTION[V]	6.30 - 7.00	13.90 - 16.35	27.60 - 32.40
ISOLATION	REMOTE SENSING	Not provided		
	REMOTE ON/OFF	Not provided		
	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
ENVIRONMENT	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
	OUTPUT-FG	AC500V 1minute, Cutoff current = 100mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
	OPERATING TEMP., HUMID. AND ALTITUDE	-20 to +95°C, 20 - 95%RH (Non condensing) *4		
SAFETY AND NOISE REGULATIONS	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +95°C, 20 - 95%RH (Non condensing), 9,000m (30,000 feet) max		
	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis		
	IMPACT	196.1m/s ² (20G), 11ms, once each along X, Y and Z axis		
OTHERS	AGENCY APPROVALS	UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN		
	CONDUCTED NOISE	Complies with FCC-B, VCCI-B, CISPR-B, EN55011-B, EN55022-B		
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) *3		
OTHERS	CASE SIZE/WEIGHT	50 X 36 X 150mm [1.97 X 1.42 X 5.91 inches] (W X H X D) / 230g max		


*1 Refer to Instruction manual for measuring method of an electrical property.

*2 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*3 Please contact us about another class.

*4 Refer to Instruction manual 3.2 and 3.3.

Block diagram



External view




- * Tolerance ± 1 [± 0.04]
- * Weight : 230g max
- * Dimensions in mm, []=inches
- * PCB material / thickness : FR-4 / 1.6mm [0.06]
- * Base plate material / thickness : Aiuminum / 3.0mm [0.12]
- * Screw tightning torque M3 : 0.9N $\cdot$ m (9.2kgf $\cdot$ cm) max
- * Please connect safety ground to the base plate in $\phi 4.5$ [$\phi 0.177$] hole.

SNTUNS100

SNTUN S 100 F 05 - ☐

① ② ③ ④ ⑤ ⑥



Recommended EMI/EMC Filter
NAC-04-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* The EMI/EMC Filter is recommended
to connect with several devices.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal Input
- ⑤ Output voltage
- ⑥ Optional
- C : with Coating
- J : Connector type

MODEL	SNTUNS100F05	SNTUNS100F12	SNTUNS100F24
MAX OUTPUT WATTAGE[W]	100.0	100.8	100.8
DC OUTPUT	5V 20A	12V 8.4A	24V 4.2A

SPECIFICATIONS

	MODEL	SNTUNS100F05	SNTUNS100F12	SNTUNS100F24
INPUT	VOLTAGE[V]	AC85 - 264 1 ϕ (Please refer to the instruction manua 1.1 and 3.2)		
	CURRENT[A]	ACIN 100V 1.3typ (Io=100%)		
		ACIN 200V 0.7typ (Io=100%)		
	FREQUENCY[Hz]	50/60 (47 - 63)		
	EFFICIENCY[%]	ACIN 100V 79typ	81typ	82typ
		ACIN 200V 82typ	83typ	84typ
	POWER FACTOR (Io=100%)	ACIN 100V 0.95typ		
		ACIN 200V 0.90typ		
OUTPUT	INRUSH CURRENT[A]	ACIN 100V 20yp (Io=100%) (At cold start) (Ta=25°C)		
		ACIN 200V 40typ (Io=100%) (At cold start) (Ta=25°C)		
	LEAKAGE CURRENT[mA]	0.4/0.75 (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60950-1 and DEN-AN)		
	VOLTAGE[V]	5	12	24
	CURRENT[A]	20	8.4	4.2
	LINE REGULATION[mV]	10max	24max	48max
	LOAD REGULATION[mV]	150max	100max	100max
	RIPPLE[mVp-p]	0 to +95°C *1 80max	120max	120max
		-20 to 0°C *1 140max	160max	160max
		0 to 15% Load *1 160max	240max	240max
PROTECTION CIRCUIT AND OTHERS	RIPPLE NOISE[mVp-p]	0 to +95°C *1 120max	150max	150max
		-20 to 0°C *1 200max	200max	250max
		0 to 15% Load *1 240max	300max	300max
	TEMPERATURE REGULATION[mV]	0 to +65°C 50max	120max	240max
		-20 to +95°C 100max	240max	480max
	DRIFT[mV]	*2 20max	40max	90max
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.50 - 5.50	10.80 - 13.20	21.60 - 26.40
	OUTPUT VOLTAGE SETTING[V]	5.00 - 5.15	12.00 - 12.48	24.00 - 24.96
	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
	OVERVOLTAGE PROTECTION[V]	6.30 - 7.00	13.90 - 16.35	27.60 - 32.40
ISOLATION	REMOTE SENSING	Optional (Option:K)	-	-
	REMOTE ON/OFF	Not provided		
	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
ENVIRONMENT	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
	OUTPUT-FG	AC500V 1minute, Cutoff current = 100mA, DC500V 50M Ω min (20 $\pm$ 15°C)		
	OPERATING TEMP., HUMID. AND ALTITUDE	-20 to +95°C (On aluminum base plate), 20 - 95%RH (Non condensing) *4		
SAFETY AND NOISE REGULATIONS	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +95°C, 20 - 95%RH (Non condensing), 9,000m (30,000 feet) max		
	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis		
	IMPACT	196.1m/s ² (20G), 11ms, once each along X, Y and Z axis		
OTHERS	AGENCY APPROVALS	UL60950-1, C-UL (CSA60950-1), EN60950-1, EN50178 Complies with DEN-AN		
	CONDUCTED NOISE	Complies with FCC-B, VCCI-B, CISPR-B, EN55011-B, EN55022-B		
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) *3		
OTHERS	CASE SIZE/WEIGHT	74 X 37 X 150mm [2.91 X 1.46 X 5.91 inches] (W X H X D) / 340g max		


*1 Refer to Instruction manual for measuring method of an electrical property.

*2 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*3 Please contact us about another class.

*4 Refer to Instruction manual 3.2 and 3.3.

Block diagram



External view



- * Tolerance ± 1 [± 0.04]
- * Weight : 340g max
- * Dimensions in mm, []=inches
- * PCB material / thickness : FR-4 / 1.6mm [0.06]
- * Base plate material / thickness : Aiuminum / 3.0mm [0.12]
- * Screw tightning torque M4 : 1.2N · m (12.2kgf · cm) max
- * Please connect safety ground to the base plate in ϕ 4.5 [ϕ 0.177] hole.



Макро Групп – это:

- дистрибьютор электронных компонентов с 1994 года
- контрактный производитель электроники с 2007 года с собственным производством в Санкт-Петербурге (компания Макро ЕМС, входит в ГК Макро Групп)
- поставщик полупроводниковых материалов
- комплексный поставщик электронных компонентов
- моделирование и производство полупроводниковых эпитаксиальных гетероструктур для задач оптоэлектроники

Головной офис расположен в Санкт-Петербурге. Собственные представительства в крупных промышленных городах России и стран СНГ.

Преимущества для наших заказчиков:

- работа по тендерам с 2012 года
- оформление банковских гарантий
- отсрочки платежей
- поставка электронных компонентов по проектным ценам
- инженерная поддержка проектов заказчиков
- сертификат системы менеджмента качества ISO 9001-2015
- необходимые сертификаты и лицензии

Данный файл получен с сайта www.macrogroup.ru